

Product data sheet for uvex rubiflex NB40S



MADE IN GERMANY 

Manufacturer address

UVEX SAFETY Gloves GmbH & Co. KG
 Elso-Klöver-Str. 6
 D-21337 Lüneburg
 uvex-safety.de

For these chemical protection gloves, a thicker cotton interlock lining is used. This makes the uvex rubiflex S suitable for many applications in which protection against chemicals and increased mechanical protection (for example against heat) is required. The special 60 or 80 cm version is also available with elasticated gauntlet end.

Features

- Ergonomic fit
- Good grip
- Very good tactile feel

Material number	98902
Sizes	8 - 11
Standard	EN 420:2003 + A1:2009, EN 388:2016, EN ISO 374-1:2016
Test chemicals	n-Heptane (J), Sodium hydroxide 40% (K), Acetic acid 99% (N), Ammonia water 25% (O), Hydrogen peroxide 30% (P), Formaldehyde 37% (T)

Performance classes in accordance with EN 388 2 1 2 1 X

Performance classes in accordance with EN 407 X 1 X X X X

Outer material	Cotton interlock
Coating	Nitrile rubber (NBR)
Coating surface area	Fully coated
Coating thickness	0.50 mm
Type	With gauntlet
Colour	Green
Glove length	40 cm