

INFORMATION SHEET

MODEL: EQ LTX

EN388:2003: 2132 **EN388:2016:** 2132X

Description

Our Model EQ LTX is a Yellow cotton coated with hard wearing Orange Latex on the palm and fingertips. Suitable for building & construction work, concrete & brick handling. This glove combines visibility, warmth and comfort. This is a very popular glove among builders, construction workers, warehouse operatives, road workers and is also known in the market as GRIP & GRAB gloves.

OTHER INFORMATION

CLEANING / MAINTENANCE

Both new and used gloves should be thoroughly inspected before being worn to ensure no damage is present. Gloves should not be left in a contaminated condition if reuse is intended in which case gloves should be cleaned as far as possible. Gloves may be washed after removal with mild detergent solution at a temperature not exceeding 40 Deg C and allowed to dry naturally, ideally with some air movement.

STORAGE

Gloves should be ideally stored in cool dry conditions in the original package and out of direct sunlight.

OBSOLESCENCE

When stored as recommended will not suffer change in mechanical properties for up to 5 years from the date of manufacture. Service life cannot be specified and depends on the application and responsibility of the user to ascertain the suitability of the glove for the intended use

GENERAL

None of the materials or processes used in the manufacture of these products are known to be harmful to the wearer. ***Gloves are coated with Latex, Users allergic to Latex should avoid using this product.***

PLEASE NOTE

The results of physical tests should help in glove selection, however it must be understood that actual conditions of use cannot be simulated and it is the responsibility of the end user and not the manufacturer to determine glove suitability for the intended use. ***Gloves are intended to protect at normal working conditions.***