









UPDATED: 14/07/2021

X5-Sumo-FC

High cut resistant liner with textured full latex coating.

A premium product offering enhanced levels of protection and manufactured from our best selling X5 yarn - A highly specialised mixture of high tenacity aramid fibre, stainless steel and other high performance fibres which ensure outstanding cut resistance. The fully coated textured latex offers increased protection against abrasion, puncture and water repellence, whilst enhancing grip and durability. Sanitized® hygiene function offers increased freshness, hygiene and odour repellence over extended usage.

Material Content: DuPont™ Kevlar® 25%, Cotton, Polyester, Steel, Glass, Nylon.

DuPont™ and Kevlar® are trademarks or registered trademarks of E.I. du Pont de Nemours and Company.



FEATURES AND TECHNOLOGY















TYPICAL INDUSTRIES



ENGINEERING











GLASS GLAZING

TECHNICAL INFORMATION

ORDER REF #	G/X5SUMO-FC
COATING MATERIAL	LATEX
PACKING	PER PACK: 5 x Pair
	PER CASE: 50 x Pair
SIZES AVAILABLE	8 (M), 9 (L), 10 (XL)
EU TYPE CERTIFICATION BY	SATRA Technology Europe Ltd, Bracetown Business Park, Clonee, Dublin, D15 YN2P, Ireland (Notified Body No. 2777)







🕕 **Fax:** +44 (0)1902 451 271



Web: www.ultimateindustrial.co.uk



Registered in England No. 2035621





TECHNICAL PRODUCT DATASHEET

CUT PROTECTION RANGE




HEAT PROTECTION



UPDATED: 14/07/2021

CERTIFICATION LEGENDS







NEWTON LEVEL

≥ 30 ≥ 22











* For details regarding permissable use exposure, see seperate

FURTHER INFORMATION

STORAGE / TRANSPORT: Keep away from direct sunlight; store in a cool dry place. Keep away from ozone sources or naked flame. Store the gloves in their original packaging. During transportation, ensure the product is well packaged and protected in order to prevent any damage.

PRECAUTIONS BEFORE USE: 1. Never use these gloves with chemicals. 2. Gloves should not be used when there is a risk of entanglement with moving machine parts. 3. Before usage and periodically during usage, inspect the gloves for any defects or imperfections. Avoid wearing damaged, dirty or worn out gloves. 4. The gloves should not come in contact with a naked flame or fire. 5. Do not subject to high speed or serrated blades. 6. Always read enclosed user instructions before using these gloves. 7. Whilst these gloves are highly cut resistant, they are not cut proof. 8. The information provided is for products in a new condition and does not reflect the actual duration of protection in the workplace. 9. Service life cannot be specified and depends on the application and the responsibility of the user to ascertain suitability of the glove for its intended use.

CONSTITUENTS / ALLERGIES: Some gloves may contain ingredients which are known to be a possible cause of allergies in sensitive persons who may develop irritant and/or allergic contact reactions. If an allergic reaction should occur seek medical advice immediately.

WARNING: This product contains natural rubber latex which may cause allergic reactions. If affected, discontinue use immediately and seek medical advice.

*SANITIZED® TREATMENT

Sanitized®: These gloves incorporate a Biocidal product. The Biocidal treatment protects against a broad spectrum of Bacteria and Fungi. The active Biocidal substance - Zinc Pyrithione - promotes freshness and inhibits odours.



For more information about this product, or to access the Declaration of Conformity or Product Certification, visit; https://www.ultimateindustrial.co.uk/hand-and-arm/cut-protection/x5-sumo-fc

If appropriate to the product, EC/EU Declaration of Conformities, relevant certification and supporting documentation are available to access through your distributor, at the above web address(s) or by contacting UCi customer services quoting the product reference code. This document and any other statement provided herein by or on behalf of UCi are given for informational purposes and do not constitute a contractual agreement nor warranty of merchantability. UCi assumes no responsibility for the suitability or adequacy of an end user's selection of product for a specific purpose. The manufacturer reserves the right to make any modifications it deems necessary. All product and company names are trademarks™ or registered® trademarks of their respective holders. DuPont™ and Kevlar® are trademarks or registered trademarks of EL du Pont de Nemours and Company. © UCi Limited, 2021





II Fax: +44 (0)1902 451 271



Web: www.ultimateindustrial.co.uk



For dulling during cut resistance test (6.2), the coupe test results are only indicative while the TDM cut resistance test (6.3) is the reference performance result.

¹ Testing carried out on the palm material. Except in cases where the glove is equal to or over 400mm - where the cuff is tested also tested. ² 'X' denotes Not Tested. ³ Where applicable, EN388:2016 scores take precedent and are ongoing. There is no correlation between coupe test levels and ISO 13997 / TDM cut test levels. Where both EN388:2016 and EN388:2003 scores are shown, the latter is shown for informational contractions. purposes only.