

Polyco[®]

PRODUCT INFORMATION

ltem Number	911
Product Colour	Red/Black
Size Range	6-12
Primary Coating Polymer	Nitrile
Grip	Microfoam Nitrile
Abrasion Level	4

FEATURES

Grip: The palm coating is infused with microfoam bubbles increasing resistance to oils and maximising grip in wet and oily handling environments

Abrasion Resistant: Achieves maximum score for abrasion resistance as defined by European Standard EN388

Flexibility: Strategically designed to offer optimum levels of flexibility and comfort without compromising protection

Closure: Elasticated knitted wrist provides a secure fit and keeps hands free from dirt and debris

Primary Coating Polymer: Nitrile

Environmental: Packed without the use of plastic; reducing the overall weight of packaging

Comfort: Seamless construction will not irritate hands

Unique Feature: SilverClear® glove formulated from silver; a powerful and proven antimicrobial agent that inhibits bacterial; fungal and viral growth. The additive will protect the gloves from microbial growth but also from mould and bad odours avoiding premature material degradation and discoloration.

SECTORS

Automotive • Construction & Utility • Engineering and Manufacturing • Warehousing, Transport and Logistics • Waste Management and Local authority



STANDARDS





4121X

STORAGE INSTRUCTIONS

Store in dry conditions, away from direct sunlight and extreme heat. You are advised to retain the packaging for reference. Always inspect gloves prior to use and do not use if damaged or showing signs of wear.

DISPOSAL INSTRUCTIONS

Dispose of responsibly and in line with local guidance.

PACKING

10 pair per polybag 60 pairs per case 85 cases per pallet susable Glo

For further technical information, please contact Customer Services on 0333 320 8550 or the Technical team on 0333 320 8555





Size	Outer Packaging Barcode
6	05010699842411
7	05010699841506
8	05010699841513
9	05010699841520
10	05010699841537
11	05010699842480

For further technical information, please contact Customer Services on 0333 320 8550 or the Technical team on 0333 320 8555