

## RUN-R PLANET 100 LOW //



100 %  
metal  
free



ART. NO. 67073

EN ISO 20345:2011 S1P SRC | EN ISO 20345:2022 S1 PL FO SR

SIZES 35 - 48

## APPLICATIONS //

trades men, light industry, warehousing and logistics, manufacturing, automotive, electronics industry, dry environments

## TECHNICAL SPECIFICATIONS //

- PU2D **sole**, very lightweight, highly flexible, excellent shock absorption, excellent levels of grip (SR), oil, hydrocarbon & chemical-resistant | grooves at the back of the heel for a better grip when the heel first touches the ground & deep grooves for better grip in the forefoot area | pronounced heel & GRIPSTEP profil for ladders and stairs
- 100% recycled polyester **upper** | TPU film in forefoot for enhanced durability | easy lock system – speed lace system
- 52% of recycled polyester and 18% of bamboo fibres **lining** for excellent breathability
- breathable textile **tongue** | stretch gussets help keep dirt and liquid out
- metal-free **toe cap** | lighter than steel | conducts less heat and cold than a metal toe cap
- metal-free **penetration-resistant midsole** | light and flexible | conducts less heat and cold than a metal sole | protects 100% of the surface of the foot | 100% recycled fibres
- **removable insole** | anatomically shaped with forefoot and heel shock absorbers | 8% of recycled polyester top layer for better abrasion resistance & durability | very high moisture absorption capacity & fast drying | bottom layer made from 67% recycled PU foam | washable at 30°C enhances hygiene
- **sizing system**: french (EU) | width 11
- **weight**: 500 g per foot, in size 42

## **GENERAL FEATURES //**

- made from 23% recycled materials according to EN ISO14021
- 100% metal-free
- free of harmful substances according to the uvex group's own list of prohibited substances, exceeding the requirements of REACH regulations
- meets the ESD specification with discharge resistance less than 35 Megaohms
- certified for use with the XSole connected insole for line worker protection

Information: Values are rounded to two decimal places • Calculation of transport: Transport of the product incl. sales surcharge of the product group Calculation method: IPCC 2021 GWP 100a (based on ISO 14067) SimaPro with corresponding databases. These CO2 values are valid at the time of calculation and may be subject to change. • Scope: cradle-to-customer • Unit: kg CO2e  
Date created : 09:2023