

MS 10 LOW //







Article ID: 67603

EN ISO 20345:2011 S1P HRO SRC | EN ISO 20345:2022 S1 PL FO HRO SR

Sizes: 36-48

APPLICATIONS //

logistics | transport | industry | services | public administration | craft industries | second fit trades | dry environments

TECHNICAL SPECIFICATIONS //

- sole: MACSOLE® SPORT rubber | excellent levels of grip (SR) | oil, hydrocarbon & chemical-resistant | resistance to contact heat up to 300°C (HRO) | excellent grip qualities with its tread pattern that disperses surface debris & increases ground-bearing surfaces to reduce slip risk
- **intermediate sole**: new MACFOAM technology in Phylon offering high performance shock absorption & cushioning | lightweight, flexible & durable, the sole performance will last the life of the shoe
- upper: textile | TPU scuff cap helps prolong product life | TPU on the back for enhances durability
- lining: 3D mesh polyester, excellent breathability & quick drying
- tonque: textile further enhances climate management | qussets help keep dirt & liquid out
- ankle padding: flexible & compact foam around ankle
- toe cap: metal-free | lighter than steel | does not conduct heat & cold compared to a metal toe cap
- penetration-resistant midsole: metal-free | light & flexible | does not conduct heat & cold compared to a
 metal sole | protects 100% of the surface of the foot
- **insole**: removable | textile top layer for better abrasion resistance, very high moisture absorption capacity & fast drying | bottom layer made from open cell foam | washable at 30°C enhances hygiene
- size system: French (EU) | width 11
- weight: 460 g in size 42