

Product data sheet uvex silv-Air 2110 FFP1 NR D



Product information

Product features	 Particle-filtering cup shape mask with exhalation valve Protection level FFP1 Soft material edges for high wearing comfort Continuous head band for a comfortable and secure fit Exhalation valve reduces breathing resistance and build-up of heat and moisture in the mask Flexible and adjustable nose clip Compatible with uvex safety eyewear Soft sealing lip guarantees a secure, comfortable sealed position of the mask Mask fulfils the requirements of the dolomite dust test (D) 	
Materials	Headband:textileNose clip:aluminumFilter/mask:Melt Blown PP, PolyesterSealing lip:PVC foamValve:ABS	
Weight	19 g	
Standard	EN 149:2001 + A1:2009	

Versions

Article number	Colour/Version	Retail unit
8732.110	cup shape mask FFP1, white with valve	15 pcs. per box
8752.110	cup shape mask FFP1, white with valve	3 pcs. per bag

Packaging sizes

Box	approx. 137 x 137 x 225 mm
Outer Carton	approx. 560 x 430 x 250 mm

Maximum breathing resistance acc. to EN149 in mbar

	Inhalation resistance 301/min.	Inhalation resistance 951/min.	Exhalation resistance 1601/min.
FFP1	0,6	2,1	3,0
FFP2	0,7	2,4	3,0
FFP3	1,0	3,0	3,0

Areas of use*

The respiratory protection mask can be	Particles (neither toxic nor associated with
used against solid, aqueous and non-volatile	fibrosis), Agriculture, hay, food industry,
liquid aerosols up to 4 times the respective	grain, flour, graphite, chalk, marble, rust.
limit values.	

*Please note that the above mentioned areas of use are examples only. The selection of PPE needs to be carried out by a competent person, in conjunction with relevant and current legislation.

All respiratory protective devices fall into PPE category III (high risks).

Uvex accepts no liability for any possible harm or damage which may result from this information. This data sheet does not replace a detailed risk assessment nor seeking specialist advise.

UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189, D-90766 Fürth