

Product data sheet uvex silv-Air 2312 FFP3 NR D



Product information

| | |
|-------------------------|--|
| Product features | <ul style="list-style-type: none"> • Particle-filtering cup shape mask with exhalation valve • Protection level FFP3 • Ergonomically for smaller faces • Soft material edges for more high wearing comfort • 4-point headband attachment allows an individual and secure fit • Exhalation valve reduces breathing resistance and build-up of heat and moisture in the mask • Flexible and adjustable nose clip • Compatible with uvex safety eyewear • Soft sealing lip guarantees a secure, comfortable sealed position of the mask • Mask fulfils the requirements of the dolomite dust test (D) |
| Materials | Headband: textile Nose clip: aluminum Headband clips: PP Filter / mask: Melt Blown PP, Polyester Sealing lip: PVC foam Valve: ABS |
| Weight | 29 g |
| Standard | EN 149:2001 + A1:2009 |

Versions

| Article number | Colour/Version | Retail unit |
|----------------|--|-----------------|
| 8732.312 | cup shape mask FFP3, white with valve | 15 pcs. per box |
| 8752.312 | cup shape mask FFP3, white with valve | 2 pcs. per bag |
| 8732.310 | cup shape mask FFP3, white with valve, standard size | 15 pcs. per box |

Packaging sizes

| | |
|--------------|----------------------------|
| Box | approx. 265 x 175 mm |
| Outer Carton | approx. 572 x 537 x 280 mm |

Maximum breathing resistance acc. to EN149 in mbar

| | Inhalation resistance 30l/min. | Inhalation resistance 95l/min. | Exhalation resistance 160l/min. |
|-------------|-----------------------------------|-----------------------------------|------------------------------------|
| FFP1 | 0,6 | 2,1 | 3,0 |
| FFP2 | 0,7 | 2,4 | 3,0 |
| FFP3 | 1,0 | 3,0 | 3,0 |

Areas of use*

| | |
|--|--|
| The respiratory protection mask can be used against solid, aqueous and non-volatile liquid aerosols up to 30 times the respective limit values. | Woodworking, hard wood, chromium, asbestos (short periods of work), stainless steel, lead, welding, dust that contain beryllium, arsenic, cadmium or cobalt. Medical waste disposal, fungal spores, legionella bacteria, infections, viruses, bacteria, enzyme, nanoparticles. |
|--|--|

*Please note that the above mentioned areas of use are examples only. The selection of PPE needs to be carried out by a competent person, in conjunction with relevant and current legislation.

All respiratory protective devices fall into PPE category III (high risks).

Uvex accepts no liability for any possible harm or damage which may result from this information.
This data sheet does not replace a detailed risk assessment nor seeking specialist advice.

UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189, D-90766 Fürth