

# Breathing Protection

02.03.2021

### Product data sheet uvex silv-Air 3200 FFP2 NR D





## **Product information**

Product features	<ul> <li>Particle-filtering flat fold mask without valve</li> <li>Protection level FFP2</li> <li>Soft material edges for high wearing comfort</li> <li>Continuous head band for a comfortable and secure fit</li> <li>Flexible and adjustable nose clip</li> <li>The masks are individually packed</li> <li>Soft sealing lip guarantees a secure, comfortable sealed position of the mask</li> <li>Compatible with uvex safety eyewear</li> <li>Mask fulfils the requirements of the dolomite dust test (D)</li> </ul>	
Materials	Headband: textile Nose clip: PP Headband clips: PP	
	Filter/mask: Melt Blown PP, Polyester	
	Sealing lip: EVA foam	
Weight	10 g	
Standard	EN 149:2001 + A1:2009	

### **Versions**

Article number	Colour/Version	Retail unit
8733.200	Flat fold mask FFP2, white without valve	30 pcs. per box
8753.200	Flat fold mask FFP2, white without valve	3 pcs. per bag

## **Packaging sizes**

- aonaging oile o	
Box	approx. 210 x 140 x 125 mm
Outer Carton	approx. 540 x 430 x 230 mm

### Maximum breathing resistance acc. to EN149 in mbar

	Inhalation resistance	Inhalation resistance	Exhalation resistance
	30I/min.	95I/min.	160I/min.
FFP1	0,6	2,1	3,0
FFP2	0,7	2,4	3,0
FFP3	1,0	3,0	3,0

#### Areas of use\*

Woodworking, softwood, cement, metal,	
smog, fine dust, concrete, iron dust, ash,	
otton dust, fluoride, carbon fibres, gypsum,	
fibre glass, copper, nickel, soot, pollen,	
ouse dust, pet hair.	
n o b	

<sup>\*</sup>Please note that the above mentioned areas of use are examples only. The selection of PPE needs to be carried out by a competent person, in conjunction with relevant and current legislation.

All respiratory protective devices fall into PPE category III (high risks).

Uvex accepts no liability for any possible harm or damage which may result from this information. This data sheet does not replace a detailed risk assessment nor seeking specialist advise.