

Breathing Protection

02.03.2021

Product data sheet uvex silv-Air 3110 FFP1 NR D



Product information

Product features	 Particle-filtering flat fold mask with exhalation valve Protection level FFP1 Soft material edges for high wearing comfort Continuous head band for a comfortable and secure fit Exhalation valve reduces breathing resistance and build-up of heat and moisture in the mask Flexible and adjustable nose clip Soft sealing lip guarantees a secure, comfortable sealed position of the mask The masks are individually packed Compatible with uvex safety eyewear Mask fulfils the requirements of the dolomite dust test (D) 	
Materials	Headband: textile Nose clip: PP Headband clips: PP	
	Filter / mask: Melt Blown PP, Polyester	
	Sealing lip: EVA foam	
	Valve: ABS	
Weight	14 g	
Standard	EN 149:2001 + A1:2009	

Versions

Article number	Colour/Version	Retail unit
8763110	Flat fold mask FFP1, white with valve	15 pcs. per box
8743110 Flat fold mask FFP1, white with valve		3 pcs. per bag

Packaging sizes

Box	approx. 210 x 140 x 125 mm
Outer Carton	approx. 540 x 430 x 230 mm

Maximum breathing resistance acc. to EN149 in mbar

	Inhalation resistance	Inhalation resistance	Exhalation resistance
	30I/min.	95l/min.	160I/min.
FFP1	0,6	2,1	3,0
FFP2	0,7	2,4	3,0
FFP3	1,0	3,0	3,0

Areas of use*

Particles (neither toxic nor associated with
fibrosis), Agriculture, hay, food industry,
grain, flour, graphite, chalk, marble, rust.

^{*}Please note that the above mentioned areas of use are examples only. The selection of PPE needs to be carried out by a competent person, in conjunction with relevant and current legislation.

All respiratory protective devices fall into PPE category III (high risks).

Uvex accepts no liability for any possible harm or damage which may result from this information. This data sheet does not replace a detailed risk assessment nor seeking specialist advise.