

Product data sheet

**uvex pronamic alpine/
uvex pronamic alpine Mips®
uvex pronamic alpine E/
uvex pronamic alpine E Mips®**



Product characteristics:

- Multi-standard helmet that meets the requirements of EN 397 and EN 12492
- Mips® brain protection system integrated in the industrial safety helmet optional available
- Side Euroslot adapters (30 mm) for attaching earmuffs
- Four retaining clips for fitting head torches or goggles
- Additional elements allow our wide range of accessories to be attached to the helmet
- Air vents for maximum ventilation
- Closed helmet shell for work in low-voltage areas (uvex pronamic alpine E)
- Maximum field of vision due to design-optimized brim geometry
- Versatile and adjustable suspension harness with stepless wheel ratchet system
- EPS inner shell ensures excellent fit and comfort
- EN 12492 forked chin strap (art. no. 9790351) included in the standard scope of delivery, EN 397 version (art. no. 9790021) sold separately as an accessory
- replaceable hygiene kits 9790350 and 9790352 (Mips®)

Standards and requirements:

The uvex pronamic alpine series meets the requirements of Regulation 2016/425 and is CE marked.

They meet the harmonized standards EN 12492:2012 (uvex pronamic alpine E: except requirement 4.1.4 ventilation), EN 50365:2002 (uvex pronamic alpine E) and EN 397:2012+A1:2012 as well as their optional requirements MM (Molten Meltal), LD (increased lateral stiffness) and low temperatures (-30°C).

In addition, the products also meet the requirements according to UKCA.

This PPE is subject to the conformity assessment procedure and is monitored by:

CE:

PZT GmbH, Bismarckstraße 264 B,
26389 Wilhelmshaven, Germany
(notified body number 1974)

The applicable jurisdiction can be found on the Declaration of Conformity.
You can find this under: uvex-safety.com/ce

Technical data:

Sizes:	51 to 63cm
Interior:	EPS-Inner shell/ Mips®-Inner shell
Weight:	505g (Standard)/ 535g (Mips®)

Materials:

Helmet shell:	ABS
Interior:	EPS
Headband:	PP
Sweatband:	Plastic
Padding:	Plastic

Use and storage:

Operating temperature:	-30 °C to +50 °C
Operating time:	4 years from the date of first use
Recommended storage conditions:	Store helmet dry (room temperature) and out of sunlight
Storage time:	4 years from the date of production

Variants/colors:

Article-Nr.	Designation	Color	Packaging unit
9735030	uvex pronamic alpine white	white	1 piece
9735130	uvex pronamic alpine hi-viz yellow	hi-viz yellow	1 piece
9735134	uvex pronamic alpine yellow	yellow	1 piece
9735230	uvex pronamic alpine hi-viz orange	hi-viz orange	1 piece
9735330	uvex pronamic alpine red	red	1 piece
9735430	uvex pronamic alpine green	green	1 piece
9735530	uvex pronamic alpine blue	blue	1 piece
9735930	uvex pronamic alpine black	black	1 piece
9735031	pronamic alpine Mips® white	white	1 piece
9735131	pronamic alpine Mips® hi-viz yellow	hi-viz yellow	1 piece
9735231	pronamic alpine Mips® hi-viz orange	hi-viz orange	1 piece

uvex pronamic alpine E

Article-Nr.	Designation	Color	Packaging unit
9736030	uvex pronamic alpine E white	white	1 piece
9736130	uvex pronamic alpine E hi-viz yellow	hi-viz yellow	1 piece
9736230	uvex pronamic alpine E hi-viz orange	hi-viz orange	1 piece
9736031	pronamic alpine E Mips® white	white	1 piece
9736131	pronamic alpine E Mips® hi-viz yellow	hi-viz yellow	1 piece
9736231	pronamic alpine E Mips® hi-viz orange	hi-viz orange	1 piece

Accessories:

Article-Nr.	Designation	Packaging unit
9790350	Hygiene set pronamic alpine	1 set
9790351	Chin strap EN 12492 pronamic alpine	1 piece
9790352	Mips® hygiene set pronamic alpine	1 set
9790021	Chin strap EN 397	1 piece
9790022	Chin strap-Clip	1 piece
	All uvex hearing protection solutions with helmet connection	
	Visors which are specified for the pronamic alpine	
	All helmet lamps from the uvex range	

UVEX ARBEITSSCHUTZ GMBH
Wuerzburger Str. 181-189
90766 Fuerth, GERMANY
T: +49 (0) 911 97 36 0
E: serviceteam@uvex.de
I: uvex-safety.de