

Chemmaster

Jacket with collar and elasticated wrists

Chemmaster provides excellent resistance to various acids, alkalis, and industrial chemicals due to its tough and durable 380gm² double coated PVC material. This makes it an ideal choice for a wide range of chemical handling operations.

KEY FEATURES

- ▲ Double storm facing stud closure for increased protection
- ▲ Ring-pull zip for easy donning and doffing when wearing gloves
- ▲ Elasticated wrists ensure a snug and secure fit
- ▲ Raglan sleeve for greater freedom of movement
- ▲ Garment can be reused if not contaminated or damaged
- ▲ Stitched and high frequency welded seams
- ▲ Tested to EN 14605 and ASTM F903



COLOUR AVAILABLE



STANDARDS



EN 14605:2005
+A1:2009
Type PB [4]

ASTM F903
Resistance to Penetration by liquids.

US TESTING DATA

Property	Test Method	Result
Basis Weight	ASTM D3776	380 g/m ²
Resistance to penetration - Sodium Hydroxide (50%)	ASTM F903 Procedure A	Pass
Resistance to penetration - Hydrochloric Acid (37%)	ASTM F903 Procedure A	Pass
Resistance to penetration - Sodium Hypochlorite (15%)	ASTM F903 Procedure A	Pass

SUITABLE INDUSTRIES & APPLICATIONS



- ▲ Chemical Cleaning
- ▲ Chemical Road Freight
- ▲ Chemical Site Handling
- ▲ Heavy Industry
- ▲ Oil and Gas
- ▲ Petrochem Refining
- ▲ Shipping
- ▲ Tank Cleaning

Chemmaster

Jacket with collar and elasticated wrists

PRODUCT OPTIONS

Item	Code	Colour	Hood	Elasticated Waist	Elasticated Wrists	Tie Closure at waist	Adjustable Neck Buckle
Apron	CMA 36X24	Green	-	-	-	✓	✓
Jacket	CMJH-EW	Green	✓	-	✓	-	-
Trouser	CMTE	Green	-	✓	-	-	-
Sleeve	CMS15	Green	-	-	✓	-	-



CMTE

CMA 36X24

CMS15

SIZING - (Wearer's Measurements)

Size	Body Height (cm)	Chest (cm)	Waist (cm)	Inside Leg (cm)
S	166-170	90-98	81-89	73
M	170-174	98-106	89-97	75
L	174-179	106-114	97-104	78
XL	179-184	114-122	104-112	81
2XL	179-184	122-130	112-120	81
3XL	179-184	130-138	120-128	81
4XL	179-184	138-146	128-136	81

STORAGE AND MAINTENANCE

We recommend storing Chemmaster garments in their original packaging, away from UV sources. After use, please follow the care instructions provided on the label. To remove any contamination, rinse the Chemmaster clothing with cold water and allow it to drip dry in a shaded area, away from UV sources. It is advisable to store Chemmaster clothing in a cool, dry, and clean environment.

NOTE: For hygiene purposes, it is recommended that the garment be worn by the same individual.

CHEMICAL RESISTANCE DATA

For chemical permeation data, please contact our sales department at sales@globusgroup.com.

COMPLIANCE STATEMENT - UK (UKCA)/EU (CE)

Product conforms to the requirement of: UK Regulation 2016/425 on PPE, brought into UK Law and amended & Regulation (EU) 2016/425 of the European Parliament and of the Council as Personal Protective Equipment (PPE).

Type-Examination, (Module B), Certificates issued by:

UK – SGS UK Ltd., Rossmore Business Park, Ellesmere Port, Cheshire, CH65 3EN, UK. [A.B. No. **0120**].

EU – SGS Fimko Oy, Takomotie 8, FI-00380, Helsinki, Finland. [N.B. No. **0598**].

PPE is subject to the conformity assessment procedure, conformity to type based on Quality Assurances of the production process, (Module D), under the surveillance of the Approved/Notified Body(ies):

UK – SGS UK Ltd., Rossmore Business Park, Ellesmere Port, Cheshire, CH65 3EN, UK. [A.B. No. **0120**].

EU – SGS Fimko Oy, Takomotie 8, FI-00380, Helsinki, Finland. [N.B. No. **0598**].

Economic Operator [EU]: Globus EMEA Ltd., 51 Dawson Street, Dublin, D02 AN25, Ireland.

© 2023 Skytec - Please note that all information given in this document is intended to be useful and informative and is correct to the best of our knowledge at time of print. No liability can be accepted for inaccuracies or omissions. The right is reserved to amend this information without prior notice. All our technical files, style descriptions, presentations, designs and drawings, give the latest update of the standards and design or style features of each product. However, delivered products may comply with previous standards, design or style features. For that Alpha disclaims any liability whatsoever. Contact our sales for full information if specific requirements are needed.

ALPHA SOLWAY LTD

Factory 1, Queensberry Street, Annan, Dumfriesshire, Scotland. DG12 5BL. UK.
www.globusgroup.com | T: +44 (0) 161 877 4747 | E: sales@globusgroup.com

SKY-DS-CMJC-EW-0923_2

GLOBUS